



Color Variants

AC200161
Stainless steel and glass
Width 52 cm

AC200161
Canopy extractor 200 series
Stainless steel and glass
Width 52 cm
Air extraction/recirculation

Can be integrated invisibly in upper cabinet
Energy-saving, low-noise fan
Rim extraction with flat and easy-to-clean glass cover
Dimmable, neutral white LED light for ideal illumination of the whole cooktop
Air extraction or recirculation system
Energy efficiency class A++

Output

Performance and noise level, output level 3/Intensive:
Air output according to DIN EN 61591.
Sound power level according to EN 60704-3.
Sound pressure level according to EN 60704-13.
Air extraction:
540 / 730 m³/h.
64 / 70 dB (A) re 1 pW.
51 / 57 dB (A) re 20 µPa.
Air recirculation:
530 / 690 m³/h.
72 / 77 dB (A) re 1 pW.
59 / 64 dB (A) re 20 µPa.
Odour reduction air recirculation 92 %.

Features

Three electronically controlled power levels and an intensive mode.
Remote control is available as a special accessory.
Interval ventilation, 6 min.
Run-on function, 6 min.
Grease filter saturation indicator.
Metal grease filter, dishwasher-safe.
Glass filter cover.
Neutral white LED light (4000 K), dimmable.
Lamp output 2 x LED spot 1W.
Illuminance: 244 lx
Fan technology with highly efficient, brushless DC motor.

Product rating

Energy efficiency class A++ at a range of energy efficiency classes from A++ to E.
Energy consumption 29.6 kWh/year.
Ventilation efficiency class A.
Illumination efficiency class A.
Grease filter efficiency class D.
Sound level min. 44 dB / max. 64 dB normal mode.

Planning notes

Patented air recirculation module with activated charcoal filter can be installed in the upper cabinet. The activated carbon filter can be changed from the front by simply pulling out the filter drawer.
The door of the upper cabinet must be fully open in order to change the activated charcoal filter.
Can be integrated invisibly in upper cabinet.
Vario cooktops with intensive production of vapours like VR/VP/VF should be placed in the middle beneath the cooker hood (in this case air recirculation is not recommended).
Clearance above gas appliances min. 65 cm (more than total load gas 12 kW min. 70 cm).
Clearance above electric appliances min. 50 cm.

Characteristics

Product name/family
Color chimney
Typology
Traditional
Approval certificates
CE, Eurasian, G-Mark, Ukraine
Length of electrical supply cord (cm)
100
Required niche size for installation (HxWxD)
418mm x 496.0mm x 264mm
Height of the chimney (mm)
Height of product, without chimney (mm)
Minimum distance above an electric hob
500
Minimum distance above a gas hob
650
Net weight (kg)
10.662
Type of control
Electronic
Number of speed settings
Maximum output air extraction (m³/h)
540
Boost position output recirculating (m³/h)
690.0
Maximum output recirculating air (m³/h)
530
Boost position air extraction (m³/h)
730
Number of lights (Stck)
2
Noise level (dB(A) re 1 pW)
64
Diameter of air outlet (mm)
120 / 150
Grease filter material
Washable aluminium
EAN code
4242006285500

Consumption and connection features

Connection rating (W)
172
Current (A)
3
Voltage (V)
220-240
Frequency (Hz)
50
Plug type
Gardy plug w/ earthing
Installation type
Built-in

created on 2020-02-14
Page 1

When installing a ventilation hood with air extraction mode and a chimney-vented fireplace, the hood's power supply line needs to feature a suitable safety switch.

Connection

Total connected load 172 W.
Connecting cable 1.0 m with plug.

