



AI240191
Island hood 200 series
Stainless steel with glass control panel
Gaggenau Anthracite
Width 90 cm
Air extraction/recirculation
Delivery with mounting kit and chimney

Stainless steel hood with glass cover fitting to oven 200 series
 Highly efficient vapour collection by moved slightly inwards filters
 Energy-saving, low-noise fan
 Perforated sheet metal filter with high grease absorption
 Function for automatic, sensor-controlled power adjustment depending on the build-up of cooking vapours
 Dimmable, neutral white LED light for ideal illumination of the whole cooktop
 Air extraction or recirculation system

Output
 Odour reduction air recirculation 85 %.

Features
 Three electronically controlled power levels and an intensive mode.
 Automatic function with sensor-controlled run-on function.
 Grease filter saturation indicator.
 Activated charcoal filter saturation indicator.
 Perforated sheet metal filter, dishwasher-safe.
 Interval ventilation, 6 min.
 Cooktop-based ventilation control (with suitable cooktop).
 Neutral white LED light (3500 K), continuously dimmable.
 Light colour in different white tones (2700 - 5000 Kelvin) can be adjusted via Home Connect.
 Lamp output 4 x FM5-04_LED_3W.
 Illuminance 650 lx continuously dimmable.
 Fan technology with highly efficient, brushless DC motor.
 Integrated sound insulation for quiet operation.
 Airflow-optimised vapour collection area with slightly inward facing filters.
 The package includes an one-way flap.
 Easy mounting system for simple installation and alignment.
 Integrated WiFi module for digital services (Home Connect).
 The availability of the Home Connect functionality depends on the availability of the Home Connect Services in your country. Home Connect Services are not available in every country – for further information please check: www.home-connect.com

Product rating
 Energy efficiency class A at a range of energy efficiency classes from A++ to E.
 Energy consumption 48.8 kWh/year.
 Ventilation efficiency class A.
 Illumination efficiency class A.
 Grease filter efficiency class B.
 Sound level min. 43 dB / max. 64 dB normal mode.

Planning notes
 The package includes the mounting kit and the two-part chimney with the dimensions from 664 mm to 844 mm. Individual planning solutions can be implemented using the special accessory chimney extension AD200326 in combination with mounting kit extension AD223346. Special chimney types are available upon request.

Characteristics
Product name/family
Color chimney
Typology
 Chimney
Approval certificates
 CE, Eurasian, G-Mark, Ukraine, VDE
Length of electrical supply cord (cm)
 130
Required niche size for installation (HxWxD)
Height of the chimney (mm)
 664-844/744-964
Height of product, without chimney (mm)
 80
Minimum distance above an electric hob
 550
Minimum distance above a gas hob
 650
Net weight (kg)
 32.529
Type of control
 Electronic
Number of speed settings
Maximum output air extraction (m3/h)
 642
Boost position output recirculating (m3/h)
 530.0
Maximum output recirculating air (m3/h)
Boost position air extraction (m³/h)
 988
Number of lights (Stck)
 4
Noise level (dB(A) re 1 pW)
 64
Diameter of air outlet (mm)
 120 / 150
Grease filter material
 Washable stainless steel
EAN code
 4242006281076

Consumption and connection features
Connection rating (W)
 272
Current (A)
 10
Voltage (V)
 220-240
Frequency (Hz)
 60; 50
Plug type
 Gardy plug w/ earthing
Installation type
 Island

created on 2020-02-14
 Page 1

Clearance above gas appliances min. 65 cm (more than total load gas 12 kW min. 70 cm).
 Clearance above electric appliances min. 55 cm.
 The recirculation module with activated charcoal filter can be installed on the telescopic chimney.
 When installing a ventilation hood with air extraction mode and a chimney-vented fireplace, the hood's power supply line needs to feature a suitable safety switch.

Connection
 Total connected load 272 W.
 Connecting cable 1.3 m with plug.
 Power consumption standby/display off 0.5 W.
 Power consumption standby/network 2 W.
 Please check the user manual for how to switch off the WiFi module.

Color Variants
 AI240191
 Stainless steel with glass control panel
 Gaggenau Anthracite
 Width 90 cm

Optional accessories
 AA200112

Installation Accessories
 AD220396
 Ceiling collar for air ducts
 Stainless steel