



#### Color Variants

AW442120  
stainless steel  
Width 120 cm

AW442120  
Wall-mounted hood 400 series  
stainless steel  
Width 120 cm  
Air extraction/recirculation  
Motorless  
Delivery without chimney

Professional technology hood combined with classic Gaggenau design  
Highly efficient extraction of cooking vapours due to large vapour collection area  
Motorless, can be combined with Gaggenau BLDC remote fan units  
Angled baffle filter with high grease absorption  
Function for automatic, sensor-controlled power adjustment depending on the build-up of cooking vapours  
Air extraction or recirculation system  
Recirculation module with activated charcoal filter: Silent and highly efficient air recirculation solution with odour reduction comparable to air extraction and long replacement intervals

#### Output

Power levels depend on the remote fan unit, see table on page XX.

#### Features

Three electronically controlled power levels and an intensive mode.  
Automatic function with sensor-controlled run-on function.  
Grease filter saturation indicator.  
Baffle filter, dishwasher-safe.  
Easy mounting system for simple installation and alignment.

#### Product rating

Energy efficiency class A.  
Energy consumption xxx.  
Ventilation efficiency class A.  
Illumination efficiency class B.  
Grease filter efficiency class B.  
Sound level min. 47 dB / max. 64 dB normal mode.

#### Planning notes

Clearance above gas appliances min. 70 cm.  
Clearance above electric appliances min. 60 cm.  
Air recirculation module with 2 activated charcoal filters is installed in the inner chimney. Special air recirculation chimneys are available for this.  
When installing a ventilation hood with air extraction mode and a chimney-vented fireplace, the power supply line of the ventilation appliance needs a suitable safety switch.

#### Connection

Total connected load 40 W.  
Connecting cable 1.8 m, pluggable.

#### Characteristics

Product name/family  
Color chimney  
Typology  
Chimney  
Approval certificates  
Australia Standards, CE, Eurasian, G-Mark, Ukraine, VDE  
Length of electrical supply cord (cm)  
175  
Required niche size for installation (HxWxD)  
Height of the chimney (mm)  
Height of product, without chimney (mm)  
102  
Minimum distance above an electric hob  
600  
Minimum distance above a gas hob  
700  
Net weight (kg)  
30.945  
Type of control  
Electronic  
Number of speed settings  
Maximum output air extraction (m<sup>3</sup>/h)  
610  
Boost position output recirculating (m<sup>3</sup>/h)  
Maximum output recirculating air (m<sup>3</sup>/h)  
Boost position air extraction (m<sup>3</sup>/h)  
Number of lights (Stck)  
3  
Noise level (dB(A) re 1 pW)  
64  
Diameter of air outlet (mm)  
150  
Grease filter material  
Washable stainless steel  
EAN code  
4242006239022

#### Consumption and connection features

Connection rating (W)  
40  
Current (A)  
10  
Voltage (V)  
220-230  
Frequency (Hz)  
60; 50  
Plug type  
Gardy plug w/ earthing  
Installation type  
Wall-mounted  
created on 2020-02-13  
Page 1