

Color Variants BOP220102 Full glass door in Gaggenau Anthracite Width 60 cm BOP220112 Full glass door in Gaggenau Metallic Width 60 cm BOP220132 Full glass door in Gaggenau Silver Width 60 cm

### Included accessories

1 x enamel baking tray. suit. pyrolitic clean. 1 x glass pan. 1 x grill shelf.

Optional accessories BA026115 Baking tray, enamelled BA046115 Glass tray BA056133 Baking stone BA226105 Grill tray, enamelled BS020002 Pizza paddle, set of 2 GN340230 Gastronorm roaster in cast aluminium

Product Variants BOP221102 Oven 200 series Full glass door in Gaggenau Anthracite Width 60 cm Left-hinged BOP220102 Oven 200 series Full glass door in Gaggenau Anthracite Width 60 cm Right-hinged

Flush installation Pyrolytic system 9 heating methods, with baking stone function TFT touch display Panel-free appliance with surface control module Electronic temperature control from 50 °C to 300 °C 76 litres net volume

## Heating methods

Hot air. Eco hot air. Top + bottom heat. Top heat. Bottom heat. Hot air+ bottom heat. Full surface grill + circulated air. Full surface grill. Baking stone function.

## Handling

Rotary knob and TFT touch display operation. Clear text display. Option to save individual recipes. Information key with use indications. Side-opening door opens up to 110° angle.

#### Features

Baking stone socket. Actual temperature display. Rapid heating. Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer. 60 W halogen light on the top. Enamelled side shelf supports with 4 tray levels, pyrolysis-safe. Home network integration for digital services (Home Connect) either via cable connection LAN (recommended) or wireless via WiFi. The availability of the Home Connect functionality depends on the availability of the Home Connect Services in your country. Home Connect Services are not available in every country - for further information please check: www.home-connect.com

# Safety

Thermally insulated door with quintuple glazing. Child lock. Safety shut-off. Cooled housing with temperature protection.

### Cleaning

Pyrolytic system. Gaggenau enamel. Heated air cleaning catalyser.

## Planning notes

Door hinge not reversible. The door panel surface of the appliance extends 21 mm from the furniture cavity. The outer edge of the door handle extends 72 mm from the furniture cavity. Necessary lateral gap between appliance door and furniture panel of min. 5 mm. Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance. When planning a corner solution, pay attention to the 110° door opening angle. Characteristics Color / Material Front Anthracite Construction type Built-in Integrated Cleaning system Pyrolytic Required niche size for installation (HxWxD) 590-590 x 560-560 x 550 Dimensions of the product (mm) 595 x 590 x 547 Dimensions of the packed product (HxWxD) (mm) 780 x 760 x 680 Control Panel Material Door Material Glass Net weight (kg) 54.600 Usable volume of cavity (I) Cooking method Baking stone function, Bottom heat, Conventional heat, Full width grill, Hot Air, Hot Air-Eco, Hot air grilling, Top heat First cavity material Oven control electronic Number of interior lights

1 Approval certificates

CE, VDE

Length of electrical supply cord (cm) EAN code 4242006279868

Consumption and connection features Number of cavities (2010/30/EC)

Energy efficiency class (2010/30/EC)

Energy consumption per cycle conventional (2010/30/EC) 1.25

Energy consumption gas oven per cycle conventional (2010/30/EC) Energy consumption per cycle forced air convection (2010/30/EC) 0.83

Energy consumption gas oven per cycle forced air convection (2010/30/EC) Energy efficiency index (2010/30/EC) 95.4

Connection rating (W) 3700

Current (A)

Voltage (V) 220-240

Frequency (Hz)

Plug type

fixed connection, no plug created on 2020-04-02 Page 1 For installation underneath cooktops: Distance between the underside of the cooktop and the top edge of the oven cavity: min. 15 mm. The planning notes for the cooktops (particularly regarding ventilation, gas/electric connection) must be taken into account. To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the corner of the housing. The main socket needs to be planned outside of the niche.

Connection

Energy efficiency class A at a range of energy efficiency classes from A+++ to D.

Total connected load 3.7 kW. Plan a connection cable. Power consumption standby/display off 0.5 W. Power consumption standby/network 1.2 W.

Time auto-standby/network 20 min.



BOP220102 Oven 200 series Full glass door in Gaggenau Anthracite Width 60 cm **Right-hinged** created on 2020-04-02 Page 2



