

Full glass door in Gaggenau Anthracite

Full glass door in Gaggenau Metallic

Gastronorm insert, stainless steel, GN

Full glass door in Gaggenau Anthracite

Color Variants

BSP220101

Width 60 cm

Width 60 cm

1 x grid.

punched.

1 x STS tray

40 mm deep

1 x STS tray.

unpunched.

40 mm deep

GN010330

GN114130

GN114230

GN124130

GN124230

Product Variants BSP221101

Width 60 cm controls at the top

Steam oven 200 Series

1/3

2/3

2/3

Included accessories

Optional accessories

BSP220111

BSP220101 Steam oven 200 Series Full glass door in Gaggenau Anthracite Width 60 cm controls at the top

Flush installation
Water tank
Large cavity
LED light source
External steam generation
Steaming without pressure with 100%
humidity from 30 °C to 100 °C
Sous-vide cooking with accurate
temperature regulation
TFT touch display
Panel-free appliance with surface
control module
Electronic temperature control from
30 °C to 100 °C
58 litres net volume

Heating methods

100 % humidity. Sous-vide cooking. Dough proofing. Defrosting. Regenerating. Low temperature steaming.

Handling

Rotary knob and TFT touch display operation. Clear text display. Personalisation of automatic programmes.

Information key with use indications. Side-opening door opens up to 110° angle.

Features

Removable 1.7 litre water tank. Water level warning. Actual temperature display. Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer.

Automatic boiling point detection. LED light on the side.

Hygienic stainless steel cooking interior.

3 tray levels.

Home network integration for digital services (Home Connect) either via cable connection LAN (recommended) or wireless via WiFi.

The availability of the Home Connect functionality depends on the availability of the Home Connect Services in your country. Home Connect Services are not available in every country – for further information please check: www.home-connect.com

Safety

Child lock. Safety shut-off. Cooled housing with temperature protection.

Cleaning

Cleaning aid.
Descaling programme for the steam generator.

Planning notes

Door hinge not reversible. No other electrical appliances should be installed above the BS. The door panel surface of the appliance extends 21 mm from the furniture cavity.

The outer edge of the door handle extends 72 mm from the furniture cavity.

Necessary lateral gap between appliance door and furniture panel of min. 5 mm.

Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.

When planning a corner solution, pay attention to the 110° door opening angle.

Characteristics

Color / Material Front

Anthracite

Construction type Built-in

Door opening

Lateral

Required niche size for installation (HxWxD)

450-450 x 560-560 x 550

Dimensions of the product (mm) 455 x 590 x 540

Dimensions of the packed product (HxWxD) (mm)

575 x 660 x 690

Control Panel Material

Door Material Glass

Net weight (kg) 40.699

Approval certificates

Australia Standards, CCC, CE, China, China ROHS 20, Eurasian, G-Mark, Ukraine, VDE

Length of electrical supply cord (cm)

EAN code

4242006278205

Consumption and connection features

Connection rating (W)

2750

Current (A)

Voltage (V) 220-240

Frequency (Hz)

Plug type

Gardy plug w/ earthing

Approval certificates

Australia Standards, CCC, CE, China, China ROHS 20, Eurasian, G-Mark, Ukraine, VDE

created on 2020-04-12 Page 1 The main socket needs to be planned outside of the niche.

The LAN port can be found at the back on the lower left side.

Connection

Total connected load 2.8 KW. Connecting cable 1.8 m with plug. Plan a LAN cable.

Power consumption standby/display on 0.8 W.

Power consumption standby/display off 0.5 W.

Power consumption standby/network 1.8 W.

Time auto-standby/display on 20 min. Time auto-standby/display off 20 min.# Time auto-standby/network 20 min. Please check the user manual for how to switch off the WiFi module.



BSP220101 Steam oven 200 Series Full glass door in Gaggenau Anthracite Width 60 cm controls at the top

created on 2020-04-12 Page 2



