



BSP221101
Steam oven 200 Series
Full glass door in Gaggenau Anthracite
Width 60 cm
controls at the top

Flush installation
Water tank
Large cavity
LED light source
External steam generation
Steaming without pressure with 100% humidity from 30 °C to 100 °C
Sous-vide cooking with accurate temperature regulation
TFT touch display
Panel-free appliance with surface control module
Electronic temperature control from 30 °C to 100 °C
58 litres net volume

Heating methods
 100 % humidity. Sous-vide cooking. Dough proofing. Defrosting. Regenerating. Low temperature steaming.

Handling
 Rotary knob and TFT touch display operation. Clear text display. Personalisation of automatic programmes. Information key with use indications. Side-opening door opens up to 110° angle.

Features
 Removable 1.7 litre water tank. Water level warning. Actual temperature display. Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer. Automatic boiling point detection. LED light on the side. Hygienic stainless steel cooking interior. 4 tray levels. Home network integration for digital services (Home Connect) either via cable connection LAN (recommended) or wireless via WiFi. The availability of the Home Connect functionality depends on the availability of the Home Connect Services in your country. Home Connect Services are not available in every country – for further information please check: www.home-connect.com

Safety
 Child lock. Safety shut-off. Cooled housing with temperature protection.

Cleaning
 Cleaning aid. Descaling programme for the steam generator.

Planning notes
 Door hinge not reversible. No other electrical appliances should be installed above the BS. The door panel surface of the appliance extends 21 mm from the furniture cavity. The outer edge of the door handle extends 72 mm from the furniture cavity. Necessary lateral gap between appliance door and furniture panel of min. 5 mm. Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance. When planning a corner solution, pay attention to the 110° door opening angle.

Characteristics
Color / Material Front
 Anthracite
Construction type
 Built-in
Door opening
 Lateral
Required niche size for installation (HxWxD)
 450-450 x 560-560 x 550
Dimensions of the product (mm)
 455 x 590 x 540
Dimensions of the packed product (HxWxD) (mm)
 575 x 660 x 690
Control Panel Material
 Glass
Door Material
 Glass
Net weight (kg)
 40.711
Approval certificates
 Australia Standards, CCC, CE, China, China ROHS 20, Eurasian, G-Mark, Ukraine, VDE
Length of electrical supply cord (cm)
 175
EAN code
 4242006278212

Consumption and connection features
Connection rating (W)
 2750
Current (A)
 16
Voltage (V)
 220-240
Frequency (Hz)
 50
Plug type
 Gardy plug w/ earthing
Approval certificates
 Australia Standards, CCC, CE, China, China ROHS 20, Eurasian, G-Mark, Ukraine, VDE

created on 2020-04-08
Page 1

The main socket needs to be planned outside of the niche. The LAN port can be found at the back on the lower left side.

Connection
 Total connected load 2.8 KW. Connecting cable 1.8 m with plug. Plan a LAN cable. Power consumption standby/display on 0.8 W. Power consumption standby/display off 0.5 W. Power consumption standby/network 1.8 W. Time auto-standby/display on 20 min. Time auto-standby/display off 20 min.# Time auto-standby/network 20 min. Please check the user manual for how to switch off the WiFi module.

Color Variants
BSP221101
 Full glass door in Gaggenau Anthracite
 Width 60 cm
BSP221111
 Full glass door in Gaggenau Metallic
 Width 60 cm
BSP221131
 Full glass door in Gaggenau Silver
 Width 60 cm

Included accessories
 1 x grid.
 1 x STS tray. punched.
 40 mm deep.
 1 x STS tray. unpunched.
 40 mm deep.

Optional accessories
GN010330
GN114130
 Gastronorm insert, stainless steel, GN 1/3
GN114230
 Gastronorm insert, stainless steel, GN 2/3
GN124130
 Gastronorm insert, stainless steel, GN 1/3
GN124230
 Gastronorm insert, stainless steel, GN 2/3

Product Variants
BSP220101
 Steam oven 200 Series
 Full glass door in Gaggenau Anthracite
 Width 60 cm
 controls at the top

Side view of BSP 220/250 above BOP

