



**BSP270101**  
**Combi-steam oven 200 series**  
**Full glass door in Gaggenau Anthracite**  
**Width 60 cm**  
**controls at the top**

**Flush installation**  
**Fixed inlet and outlet water connection**  
**Cleaning system, fully automatic**  
**Large cavity**  
**LED light source**  
**External steam generation**  
**Steaming without pressure**  
**Hot air 30 °C to 230 °C can be combined with chosen humidity level of 0%, 30%, 60%, 80% or 100%**  
**Sous-vide cooking with accurate temperature regulation**  
**Full surface grill behind glass ceramic, combinable with circulated air up to 230 °C and steam**  
**Automatic programmes**  
**Core temperature probe with estimation of cooking time**  
**Hot air fan rotates in both directions for ideal heat distribution**  
**TFT touch display**  
**Panel-free appliance with surface control module**  
**Electronic temperature control from 30 °C to 230 °C**  
**50 litres net volume**

**Heating methods**  
**Hot air + 100 % humidity. Hot air + 80 % humidity. Hot air + 60 % humidity. Hot air + 30 % humidity. Hot air + 0 % humidity. Low temperature cooking. Sous-vide cooking. Full surface grill level 1 + humidity. Full surface grill level 2 + humidity. Full surface grill + circulated air. Dough proofing. Defrosting. Regenerating.**

**Handling**  
**Rotary knob and TFT touch display operation.**  
**Clear text display.**  
**Option to save individual recipes (incl. core temperature probe).**  
**Personalisation of automatic programmes.**  
**Information key with use indications.**  
**Side-opening door opens up to 110° angle.**

**Features**  
**Full surface grill 2000 W behind glass ceramic.**  
**Steam removal.**  
**Three-point core temperature probe with automatic shut-off and estimation of cooking time.**  
**Automatic programmes.**  
**Actual temperature display.**  
**Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer.**  
**Automatic boiling point detection.**  
**LED light on the side.**  
**Hygienic stainless steel cooking interior.**  
**4 tray levels.**  
**Home network integration for digital services (Home Connect) either via cable connection LAN (recommended) or wireless via WiFi.**  
**The availability of the Home Connect functionality depends on the availability of the Home Connect Services in your country. Home Connect Services are not available in every country – for further information please check: [www.home-connect.com](http://www.home-connect.com)**

**Safety**

**Characteristics**  
**Color / Material Front**  
**Anthracite**  
**Construction type**  
**Built-in**  
**Door opening**  
**Lateral**  
**Required niche size for installation (HxWxD)**  
**450-450 x 560-560 x 550**  
**Dimensions of the product (mm)**  
**455 x 590 x 540**  
**Dimensions of the packed product (HxWxD) (mm)**  
**590 x 660 x 690**  
**Control Panel Material**  
**Glass**  
**Door Material**  
**Glass**  
**Net weight (kg)**  
**46.069**  
**Approval certificates**  
**Australia Standards, CCC, CE, China, China ROHS 20, Eurasian, G-Mark, Ukraine, VDE**  
**Length of electrical supply cord (cm)**  
**175**  
**EAN code**  
**4242006278007**

**Consumption and connection features**  
**Electrical connection rating (W)**  
**Current (A)**  
**16**  
**Voltage (V)**  
**220-240**  
**Frequency (Hz)**  
**50**  
**Plug type**  
**Gardy plug w/ earthing**  
**Approval certificates**  
**Australia Standards, CCC, CE, China, China ROHS 20, Eurasian, G-Mark, Ukraine, VDE**  
**Number of cavities (2010/30/EC)**  
**1**  
**Usable volume (of cavity) - NEW (2010/30/EC)**  
**50**  
**Energy efficiency class (2010/30/EC)**  
**A**  
**Energy consumption per cycle conventional (2010/30/EC)**  
**Energy consumption gas oven per cycle conventional (2010/30/EC)**  
**Energy consumption per cycle forced air convection (2010/30/EC)**  
**0.72**  
**Energy consumption gas oven per cycle forced air convection (2010/30/EC)**  
**Energy efficiency index (2010/30/EC)**  
**94.7**

**created on 2020-03-16**  
**Page 1**

**Child lock.**  
**Safety shut-off.**  
**Cooled housing with temperature protection.**

**Cleaning**  
**Cleaning programme, fully automatic.**  
**Descaling programme for the steam generator.**  
**Drying function.**  
**Strainer filter, removable.**  
**Demo cleaning programme.**

**Planning notes**  
**Door hinge not reversible.**  
**No other electrical appliances should be installed above the BS.**  
**At no point may the outlet hose be positioned higher than the bottom edge of the appliance. The outlet hose must also be at least 100 mm lower than the appliance outlet (see drawing "drain connection").**  
**Inlet hose can be extended once.**  
**The outlet hose must not be longer than a maximum of 5 m.**  
**The water connection (1) for the inlet hose must always be accessible and not located directly behind the appliance.**

**The connection of the outlet hose to the siphon (2) must not be directly behind the appliance and should be accessible.**  
**The descaling system GF 111 100 (3) must be installed when connecting the appliance if the water hardness exceeds 7° dH.**  
**The door panel surface of the appliance extends 21 mm from the furniture cavity.**  
**The outer edge of the door handle extends 72 mm from the furniture cavity.**  
**Necessary lateral gap between appliance door and furniture panel of min. 5 mm.**  
**Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.**  
**When planning a corner solution, pay attention to the 110° door opening angle.**  
**The main socket needs to be planned outside of the niche.**

**Connection**  
**Energy efficiency class A at a range of energy efficiency classes from A+++ to D.**  
**Total connected load 3.1 KW.**  
**Only cold water connection.**  
**Inlet hose 3.0 m with 3/4 " (26,4 mm) connection, extendable.**  
**Outlet hose (ø 24 mm) 3.0 m (HT-Hose).**  
**Connecting cable 1.8 m with plug.**  
**Plan a LAN cable.**  
**Power consumption standby/display on 0.8 W.**  
**Power consumption standby/display off 0.5 W.**  
**Power consumption standby/network 1.8 W.**  
**Time auto-standby/display on 20 min.**  
**Time auto-standby/display off 20 min.#**  
**Time auto-standby/network 20 min.**  
**Please check the user manual for how to switch off the WiFi module.**

**Color Variants**  
**BSP270101**  
**Full glass door in Gaggenau Anthracite**  
**Width 60 cm**  
**BSP270111**  
**Full glass door in Gaggenau Metallic**  
**Width 60 cm**  
**BSP270131**  
**Full glass door in Gaggenau Silver**  
**Width 60 cm**

**Included accessories**  
**1 x outlet hose 3m.**  
**1 x grid.**  
**1 x pluggable meat probe.**  
**1 x water inlet hose 3m.**  
**1 x STS tray.**  
**punched.**  
**40 mm deep.**

**Optional accessories**  
**GN010330**  
**GN114130**  
**Gastronorm insert, stainless steel, GN 1/3**  
**GN114230**  
**Gastronorm insert, stainless steel, GN 2/3**  
**GN124130**  
**Gastronorm insert, stainless steel, GN 1/3**  
**GN124230**  
**Gastronorm insert, stainless steel, GN 2/3**  
**GN340230**  
**Gastronorm roaster in cast aluminium**

**Installation Accessories**  
**GF111100**  
**Descaling and neutralising filter**  
**GF121110**  
**Filter cartridges**  
**GZ010011**  
**Aqua stop extension (2 m long)**

**Product Variants**  
**BSP271101**  
**Combi-steam oven 200 series**  
**Full glass door in Gaggenau Anthracite**  
**Width 60 cm**  
**controls at the top**

