



Color Variants

BX480112
Stainless steel-backed full glass door
Width 76 cm

Included accessories

2 x enamel baking tray.
suit. pyrolytic clean.
1 x rotary spit.
2 x grill shelf.
2 x grill tub with grid.
1 x pluggable meat probe.

Optional accessories

BA018105
Pull-out system
BA028115
Baking tray, enamelled
BA038105
Wire rack, chromium-plated
BA058115
Heating element for baking stone and
Gastronorm roaster
BA058133
Baking stone
BS020002
Pizza paddle, set of 2
GN340230
Gastronorm roaster in cast aluminium

Product Variants

BX481112
Double oven 400 series
Stainless steel-backed full glass door
Width 76 cm
Controls centered

BX480112
Double oven 400 series
Stainless steel-backed full glass door
Width 76 cm
Controls centered

Pyrolytic system
17 heating methods, with core
temperature probe, rotisserie spit
and baking stone function
Core temperature probe with
estimation of cooking time
TFT touch display
Electronic temperature control from
30 °C to 300 °C

Heating methods

Hot air.
Eco hot air.
Top + bottom heat.
Top + 1/3 bottom heat.
Top heat.
1/3 top + bottom heat.
Bottom heat.
Hot air + bottom heat.
Hot air + 1/3 bottom heat.
Full surface grill + circulated air.
Full surface grill.
Compact grill.
Baking stone function.
Roaster function.
Dough proofing.
Defrosting.
Keeping warm.

Handling

Rotary knob and TFT touch display
operation.
Clear text display.
Information key with use indications.
Side-opening door opens up to 180°
angle.

Features

Three-point core temperature probe
with automatic shut-off and estimation
of cooking time.
Rotisserie spit (lower oven).
Baking stone socket.
Actual temperature display.
Rapid heating.
Timer functions: cooking time, cooking
time end, timer, stopwatch, long-term
timer.
60 W halogen light on the top.
2x10 W halogen light on the side.
Enamelled side shelf supports with 3
tray levels, pyrolysis-safe.

Safety

Thermally insulated door with
quadruple glazing.
Child lock.
Safety shut-off.
Cooled housing with temperature
protection.

Cleaning

Pyrolytic system.
Gaggenau enamel.
Heated air cleaning catalyser.

Planning notes

Door hinge not reversible.
The façade of the appliance extends 47
mm from the furniture cavity.
When planning a corner solution, pay
attention to the 90° door opening
angle.
To achieve the 550 mm installation
depth, the connection cable needs to
follow the slanted edge on the lower
right hand corner of the housing.
The main socket needs to be planned
outside of the niche.

Connection

Energy efficiency class A at a range of
energy efficiency classes from A+++ to
D.

Characteristics

Color / Material Front
Construction type
Built-in
Integrated Cleaning system
Dimensions of the product (mm)
1428 x 752 x 547
**Dimensions of the packed product
(HxWxD) (mm)**
1600 x 755 x 840
Control Panel Material
Alu
Door Material
Stainless steel behind glass
Net weight (kg)
161.920
Usable volume of cavity (l)
110
Cooking method
Baking stone function, Bottom heat,
Conventional heat, Defrost, Dough
proving setting, Full width grill, Half
width grill, Hot Air, Hot Air-Eco, Hot air
grilling, Roaster function, Top heat,
warming
First cavity material
Enamelled
Oven control
electronic
Number of interior lights
2
Approval certificates
Australia Standards, CE, Ukraine, VDE
Length of electrical supply cord (cm)
EAN code
4242006284800

Consumption and connection features

Energy efficiency class (2010/30/EC)
A
**Energy consumption per cycle
conventional (2010/30/EC)**
1.53
**Energy consumption gas oven per cycle
conventional (2010/30/EC)**
**Energy consumption per cycle forced
air convection (2010/30/EC)**
0.96
**Energy consumption gas oven per cycle
forced air convection (2010/30/EC)**
**Energy efficiency class (2010/30/EC) -
cavity 2**
A
**Energy consumption per cycle
conventional - cavity 2 (2010/30/EC)**
1.53
**Energy consumption gas oven per cycle
conventional - cavity 2 - NEW (2010/30/
EC)**
**Energy consumption per cycle forced
air convection - cavity 2 (2010/30/EC)**
1.08
**Energy consumption gas oven per
cycle forced air convection - cavity 2
(2010/30/EC)**
Energy efficiency index (2010/30/EC)
95.0
**Energy efficiency index cavity 2
(2010/30/EC)**
106.9
Connection rating (W)
9200
Current (A)
Voltage (V)
220-240
Frequency (Hz)
50
Plug type
fixed connection, no plug

created on 2020-03-29

Page 1

Total connected load 9.2 kW.

Plan a connection cable.

BX480112
Double oven 400 series
Stainless steel-backed full glass door
Width 76 cm
Controls centered
created on 2020-03-29
Page 2

