



Color Variants

BX481112
Stainless steel-backed full glass door
Width 76 cm

Optional accessories

BA018105
Pull-out system
BA028115
Baking tray, enamelled
BA038105
Wire rack, chromium-plated
BA058115
Heating element for baking stone and
Gastronorm roaster
BA058133
Baking stone
BS020002
Pizza paddle, set of 2
GN340230
Gastronorm roaster in cast aluminium

Product Variants

BX480112
Double oven 400 series
Stainless steel-backed full glass door
Width 76 cm
Controls centered

BX481112
Double oven 400 series
Stainless steel-backed full glass door
Width 76 cm
Controls centered

Pyrolytic system
17 heating methods, with core temperature probe, rotisserie spit and baking stone function
Core temperature probe with estimation of cooking time
TFT touch display
Electronic temperature control from 30 °C to 300 °C

Heating methods

Hot air.
Eco hot air.
Top + bottom heat.
Top + 1/3 bottom heat.
Top heat.
1/3 top + bottom heat.
Bottom heat.
Hot air + bottom heat.
Hot air + 1/3 bottom heat.
Full surface grill + circulated air.
Full surface grill.
Compact grill.
Baking stone function.
Roaster function.
Dough proofing.
Defrosting.
Keeping warm.

Handling

Rotary knob and TFT touch display operation.
Clear text display.
Information key with use indications.
Side-opening door opens up to 180° angle.

Features

Three-point core temperature probe with automatic shut-off and estimation of cooking time.
Rotisserie spit (lower oven).
Baking stone socket.
Actual temperature display.
Rapid heating.
Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer.
60 W halogen light on the top.
2x10 W halogen light on the side.
Enamelled side shelf supports with 3 tray levels, pyrolysis-safe.

Safety

Thermally insulated door with quadruple glazing.
Child lock.
Safety shut-off.
Cooled housing with temperature protection.

Cleaning

Pyrolytic system.
Gaggenau enamel.
Heated air cleaning catalyser.

Planning notes

Door hinge not reversible.
The façade of the appliance extends 47 mm from the furniture cavity.
When planning a corner solution, pay attention to the 90° door opening angle.
To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the lower right hand corner of the housing.
The main socket needs to be planned outside of the niche.

Connection

Energy efficiency class A at a range of energy efficiency classes from A+++ to D.

Characteristics

Color / Material Front

Construction type

Built-in

Integrated Cleaning system

Dimensions

1428 x 752 x 547

Dimensions of the packed product (HxWxD) (mm)

1760 x 750 x 850

Control Panel Material

Alu

Door Material

Stainless steel behind glass

Net weight (kg)

160.845

Usable volume of cavity (l)

110

Cooking method

Baking stone function, Bottom heat, Conventional heat, Defrost, Dough proving setting, Full width grill, Half width grill, Hot Air, Hot Air-Eco, Hot air grilling, Roaster function, Top heat, warming

First cavity material

Temperature control

electronic

Number of interior lights

2

Approval certificates

Australia Standards, CE, Ukraine, VDE

Length of electrical supply cord (cm)

EAN code

4242006285982

Energy efficiency rating

A

Energy consumption per cycle conventional (2010/30/EC)

1.53

Energy consumption gas oven per cycle conventional (2010/30/EC)

Energy consumption per cycle forced air convection (2010/30/EC)

0.96

Energy consumption gas oven per cycle forced air convection (2010/30/EC)

Energy efficiency class (2010/30/EC) - cavity 2

A

Energy consumption per cycle conventional - cavity 2 (2010/30/EC)

1.53

Energy consumption gas oven per cycle conventional - cavity 2 - NEW (2010/30/EC)

Energy consumption per cycle forced air convection - cavity 2 (2010/30/EC)

1.08

Energy consumption gas oven per cycle forced air convection - cavity 2 (2010/30/EC)

Energy efficiency index (2010/30/EC)

95.0

Energy efficiency index cavity 2 (2010/30/EC)

106.9

Connection rating (W)

9200

Current (A)

Voltage (V)

220-240

Frequency (Hz)

50

Plug type

fixed connection, no plug

Consumption and connection features

created on 2021-02-01

Page 1

Total connected load 9.2 KW.
Plan a connection cable.

BX481112
Double oven 400 series
Stainless steel-backed full glass door
Width 76 cm
Controls centered

created on 2021-02-01
Page 2

