



CG261210
200 series gas cooktop
Stainless steel
Width 60 cm
Natural gas 20 mbar
Nozzles for liquid gas 28-30/37 mbar included

Mechanical power level regulation for 9 power levels, with exact setting and reproduction of flame size
9.75 KW with burners in a diamond-shaped arrangement

Cooking zones

1 three-ring wok burner (1550 W – 4000 W).
1 high output burner (500 W - 3000 W), suitable for pots up to max. ø 26 cm.
1 standard burner (320 – 1750 W), suitable for pots up to max. ø 20 cm.
1 economy burner (330 W – 1000 W), suitable for pots up to max. ø 16 cm.

Handling

Control knobs with cooking zone and output level markings for 9 levels.
One-handed operation.
Electric ignition.

Features

Two-part cast pan support with continuous pot surface.
Enamelled burner cover.

Safety

Thermoelectric safety pilot.

Planning notes

The cooktop can be surface-mounted.
Special nozzles can be ordered as spare parts.
Installation in a 56 cm standard niche.
Air intake from above.
Intermediate shelf is recommended.
Allow for a gas connection when planning drawer depth.
Appliance must be fixed from underneath.
A minimum clearance of at least 100 mm from adjacent heat-sensitive furniture or contact surfaces must be observed or thermal insulation fitted.
Cooktop clamping range: 30 - 50 mm.
Appliance weight: approx. 12 kg.

Connection

Total rating :Gas : 9.75 KW
electro : 1.1 W
Connecting cable 1.0 m without plug.

Characteristics

Product name/family
gas hob w integrated controls
Construction type
Built-in
Energy input
Gas
Total number of positions that can be used at the same time
4
Type of control setting devices
sword knobs
Required niche size for installation (HxWxD)
45 x 560-562 x 480-492
Width of the product (mm)
582
Dimensions of the product (mm)
45 x 582 x 520
Dimensions of the packed product (HxWxD) (mm)
141 x 651 x 578
Net weight (kg)
11.574
Gross weight (kg)
12.5
Residual heat indicator
without
Location of control panel
Hob front
Type of external control possibility
Basic surface material
Stainless steel
Color of surface
Stainless steel
Color of frame
Stainless steel
Approval certificates
CE, Ukraine
Length of electrical supply cord (cm)
100
EAN code
4242006259280

Consumption and connection features

Electrical connection rating (W)
1
Gas connection rating (W)
9750
Current (A)
3
Voltage (V)
220-240
Frequency (Hz)
60; 50

created on 2020-03-23

Page 1

Color Variants

CG261210
Stainless steel
Width 60 cm

Included accessories

1 x cross support for espresso.
1 x WOK attachment ring.

Optional accessories

WP400001
Wok pan made of multiple-layer material