



Color Variants

CI261114
Stainless steel frame
Width 60 cm

CI261114
200 series induction cooktop
Stainless steel frame
Width 60 cm

Sturdy stainless steel frame
Oval roasting zone switches on automatically
Sensor control with direct selection of output level

Cooking zones
1 induction cooking zone ø 18 cm (1800 W, with booster 3100 W), automatically switches to a 18 x 28 cm roasting zone (2000 W, with booster 3700 W).
1 induction cooking zone ø 21 cm (2200 W, with booster 3700 W).
1 induction cooking zone ø 18 cm (1800 W, with booster 3100 W).
1 induction cooking zone ø 15 cm (1400 W, with booster 2200 W).

Handling
Sensor control with direct selection of output level.
Cooking zone marking.
Electronic power control in 17 output levels.

Features
Booster function for each cooking zone.
Cooking timer for up to 99 minutes.
Short-term timer.
Options menu.
Power management.

Safety
Main switch.
Operation indicator.
Pot detection.
2 stage Hh residual heat indicator for each zone
Child lock.
Safety shut-off.

Planning notes
Operates with magnetic (induction) iron pots and pans only. For an optimal heat distribution, the use of sandwich bottom cookware is recommended. The wok pan WP 400 001 cannot be used with this appliance.
Intermediate shelf is recommended.
Appliance must be fixed from underneath.
Appliance weight: approx. 14 kg.

Connection
Total connected load 7.4 kW.
Connecting cable 1.5 m without plug.

Characteristics
Product name/family
Cooking zone ceramic
Construction type
Built-in
Energy input
Electric
Total number of positions that can be used at the same time
4
Type of control setting devices
Required niche size for installation (HxWxD)
55 x 560-560 x 490-490
Width of the product (mm)
590
Dimensions of the product (mm)
55 x 590 x 520
Dimensions of the packed product (HxWxD) (mm)
130 x 750 x 600
Net weight (kg)
14.071
Gross weight (kg)
15.3
Residual heat indicator
Separate
Location of control panel
Hob front
Type of external control possibility
Basic surface material
Ceramic
Color of surface
Black, Stainless steel
Color of frame
Stainless steel
Approval certificates
AENOR, CE
Length of electrical supply cord (cm)
150
EAN code
4242006282202

Consumption and connection features
Electrical connection rating (W)
7400
Gas connection rating (W)
Current (A)
Voltage (V)
220-240
Frequency (Hz)
50; 60

created on 2020-03-29
Page 1