



Color Variants

DF480162
fully integrated
Height 81.5 cm

Included accessories

1 x baking tray spray head.
1 x glass holder rack.
1 x GN container insert.

Optional accessories

DA041160
DA042030
Silvercare cartridge for all dishwashers

Installation Accessories

DA021000
Hinge for all fully integrated dishwashers
GZ010011
Aqua stop extension (2 m long)

DF480162

Dishwasher 400 series

fully integrated

Height 81.5 cm

8 programmes with aqua sensor and 5 options, such as Power and Intensive:
Clean and dry dishes in 57 minutes
Intensive cleaning in the lower basket while protecting glassware in the upper basket
Flexible basket system with smooth running rails on all levels and cushioned closing of the upper and lower basket
Remaining time projection onto the kitchen floor
Perfectly illuminated interior
Push-to-open function for perfect integration into handleless furniture fronts
Very quiet: 43 dB
Energy efficiency class A+++
Aqua stop with guarantee

Handling

Touch key operation.
Time delay up to 24 hours.
Remaining time projection.

Features

Perfectly illuminated interior.
Glass protection with zeolite.
Aqua sensor.
Load sensor.
Automatic detergent function.
Regeneration electronics.
Heat exchanger - Hygienic and efficient drying
Continuous flow heater.
Triple filter system, self-cleaning.
Soft lock.
Aqua stop with guarantee.
Integrated WiFi module for digital services (Home Connect).
The availability of the Home Connect functionality depends on the availability of the Home Connect Services in your country. Home Connect Services are not available in every country – for further information please check: www.home-connect.com

Programmes

8 programmes:
Auto 35 °C - 45 °C.
Auto 45 °C - 65 °C.
Auto 65 °C - 75 °C.
Intensive 70 °C.
Standard Eco 50 °C.
Night programme.
Quick wash 45 °C (29 min.).
Pre-rinse.
5 options:
Intensive.
Power.
Half Load.
Hygiene.
Extra Dry.

Features

Flexible basket system with smooth running rails on all levels and cushioned closing of the upper and lower basket.
Upper basket:
Over extension.
Rackmatic with 3 levels, adjustable in height up to 5 cm.
6 folding spines.
4 folding racks.
2 glass support bars.
Lower basket:
8 folding spines.
2 folding racks.
Dividable glass support.
Cutlery basket.

Characteristics

Water consumption (l)

9.5

Construction type

Built-in

Height of removable worktop (mm)

0

Required niche size for installation (HxWxD)

815-875 x 600 x 550

Depth with open door 90 degree (mm)

1150

Adjustable feet

Yes - front only

Maximum adjustability feet (mm)

60

Adjustable plinth

both horizontal and vertical

Net weight (kg)

51.823

Gross weight (kg)

54.0

Connection rating (W)

2400

Current (A)

10

Voltage (V)

220-240

Frequency (Hz)

50; 60

Length of electrical supply cord (cm)

175

Plug type

Gardy plug w/ earthing

Length inlet hose (cm)

165

Length outlet hose (cm)

190

EAN code

4242006277956

Consumption and connection features

Number of place settings

12

Energy efficiency class (2010/30/EC)

A+++

Energy consumption annual (kWh/

annum) - NEW (2010/30/EC)

230.00

Energy consumption (kWh)

0.80

Power consumption in left-on mode (W)

- NEW (2010/30/EC)

0.50

Power consumption in off-mode (W) -

NEW (2010/30/EC)

0.50

Water consumption annual (l/annum) -

NEW (2010/30/EC)

2660

Drying performance

A

Reference programme

Eco

Total cycle time of reference

programme (min)

195

Noise level (dB(A) re 1 pW)

43

Installation type

Full-integrated

created on 2020-03-10

Page 1

Holder for long-stemmed glasses.

Maximum dish sizes (upper/lower basket)

27/25, 24.5/27.5 or 22/31 cm respectively.

12 place setting capacity.

Maximum glass loading capacity 23 wine glasses.

Product rating

Energy efficiency class A+++ at a range of energy efficiency classes from A++ + to D.

From 9.5 l water.

From 0.8 kWh.

Noise level 43 dB (re 1 pW).

Planning notes

Height-adjustable feet.

Appliance plinth recess 100 mm (see drawing).

To display the remaining time projection, a minimum plinth protrusion must be present (40 mm + thickness of the furniture front).

The maximum plinth height must be reduced by 30 mm to provide an optimal display of the remaining time projection.

Rear feet adjustable at front.

Door weight up to 8.5 kg.

Door panel dimension dependent on plinth height of kitchen furniture.

For installation into a tall unit, ventilation openings are required (min. 200 cm²).

Connection

Total connected load 2.4 kW.

Connecting cable plugable.

Water connection with 3/4" screw joint.

Connection to hot or cold water possible.

Power consumption standby/network 2 W.

Power consumption left-on-mode 0.5 W.

Power consumption off-mode 0.5 W.

Time auto-standby/network 2 min.

Left-on-mode duration 0 min.

Please check the user manual for how to switch off the WiFi module.

GAGGENAU

