

Color Variants

DF481162 fully integrated Height 86.5 cm

Included accessories

1 x baking tray spray head.

1 x glass holder rack.

1 x GN container insert.

Optional accessories

DA041160

DA042030

Silvercare cartridge for all dishwashers

Installation Accessories

DA021000

Hinge for all fully integrated diswashers

GZ010011

Aqua stop extension (2 m long)

Dishwasher 400 series

fully integrated

Height 86.5 cm

DF481162

8 programmes with aqua sensor and 5 options, such as Power and Intensive:

Clean and dry dishes in 57 minutes Intensive cleaning in the lower basket while protecting glassware in the upper basket

Flexible basket system with smooth running rails on all levels and cushioned closing of the upper and lower basket

Remaining time projection onto the kitchen floor

Perfectly illuminated interior Push-to-open function for perfect integration into handleless furniture fronts

Very quiet: 43 dB Energy efficiency class A+++ Aqua stop with guarantee

Handling

Touch key operation. Time delay up to 24 hours. Remaining time projection.

Load sensor.

Perfectly illuminated interior. Glass protection with zeolite. Agua sensor.

Automatic detergent function.

Regeneration electronics. Heat exchanger - Hygienic and efficient

drvina Continuous flow heater.

Triple filter system, self-cleaning. Soft lock.

Aqua stop with guarantee. Integrated WiFi module for digital services

(Home Connect).

The availability of the Home Connect functionality depends on the availability of the Home Connect Services in your country. Home Connect Services are not available in every country - for further information please check: www.home-connect.com

Programmes

8 programmes: Auto 35 °C - 45 °C.

Auto 45 °C - 65 °C.

Auto 65 °C - 75 °C.

Intensive 70 °C.

Standard Eco 50 °C.

Night programme.

Quick wash 45 °C (29 min.).

Pre-rinse.

5 options:

Intensive.

Power.

Half Load. Hygiene.

Extra Dry.

Features

Flexible basket system with smooth running rails on all levels and cushioned closing of the upper and lower basket.

Upper basket:

Over extension.

Rackmatic with 3 levels, adjustable in height up to 5 cm.

6 folding spines.

4 folding racks.

2 glass support bars. Lower basket:

8 folding spines

2 folding racks.

Dividable glass support.

Cutlery basket.

Characteristics

Water consumption (I)

9.5

Construction type

Built-in

Height of removable worktop (mm)

Required niche size for installation (HxWxD)

865-925 x 600 x 550

Depth with open door 90 degree (mm) 1200

Adjustable feet

Yes - front only

Maximum adjustability feet (mm)

Adjustable plinth

both horizontal and vertical

Net weight (kg)

53,191

Gross weight (kg) 55.5

Connection rating (W)

Current (A)

Voltage (V)

220-240

Frequency (Hz)

50:60

Length of electrical supply cord (cm)

Plug type

Gardy plug w/ earthing

Length inlet hose (cm)

Length outlet hose (cm)

EAN code

4242006276850

Consumption and connection features

Number of place settings

Energy efficiency class (2010/30/EC)

Energy consumption annual (kWh/ annum) - NEW (2010/30/EC)

Energy consumption (kWh)

0.80

Power consumption in left-on mode (W) - NEW (2010/30/EC)

0.50

Power consumption in off-mode (W) -NEW (2010/30/EC)

2660

Water consumption annual (I/annum) -NEW (2010/30/EC)

Drying performance

Reference programme

Total cycle time of reference programme (min)

Noise level (dB(A) re 1 pW)

Installation type

Full-integrated created on 2020-03-06

Page 1

Holder for long-stemmed glasses. Maximum dish sizes (upper/lower basket) 29/28, 26.5/30.5 or 24/34 cm respectively. 12 place setting capacity. Maximum glass loading capacity 23

wine glasses. Product rating

Energy efficiency class A+++ at a range of energy efficiency classes from A++ + to D

From 9.5 I water.

From 0.8 kWh.

Noise level 43 dB (re 1 pW).

Planning notes

Height-adjustable feet.

Appliance plinth recess 100 mm (see

To display the remaining time projection, a minimum plinth protrusion must be present (40 mm + thickness of the furniture front).

The maximum plinth height must be reduced by 30 mm to provide an optimal display of the remaining time projection.

Rear feet adjustable at front. Door weight up to 10 kg. Door panel dimension dependent on plinth height of kitchen furniture. For installation into a tall unit, ventilation openings are required (min. 200 cm²).

Connection

Total connected load 2.4 kW. Connecting cable plugable. Water connection with 3/4" screw joint. Connection to hot or cold water possible.

Power consumption standby/network 2


Power consumption left-on-mode 0.5 W. Power consumption off-mode 0.5 W. Time auto-standby/network 2 min. Left-on-mode duration 0 min. Please check the user manual for how to switch off the WiFi module.



DF481162
Dishwasher 400 series
fully integrated
Height 86.5 cm
created on 2020-03-06

created on 2020-03-06 Page 2

Connection dimensions for a 60 cm wide dishwasher



() values with extension kit

