

Color Variants

Width 70 cm

VV200014

cooktops

Stainless steel control panel

Installation Accessories

Stainless steel connection strip

for combination with further Vario

VI270114

VI270114

Vario induction cooktop 200 series Stainless steel control panel

Width 70 cm

Can be combined with the cooktops of the Vario 200 series to a harmonic unity.

Generous control panel for comfortable and secure operation.

Cooking zones

1 induction cooking zone ø 21 cm (2200 W, with booster 3300 W). 2 induction cooking zones ø 18 cm (1800 W, with booster 2500 W). 1 induction cooking zone ø 15 cm (1400 W, with booster 1800 W).

Handling

Control knobs with cooking zone and output level markings Electronic control in 9 output levels.

Features

Cooking zone marking. Pot detection. Booster function for all cooking zones (two cooking zones - left and right can be operated simultaneously with booster function).

Safety

Residual heat indication. Operation indicator. Safety shut-off.

Planning notes

Operates with magnetic (induction) iron pots and pans only. For an optimal heat distribution, the use of sandwich bottom cookware is recommended. Immersion depth 49 mm. Cooktop clamping range: 20 - 40 mm. Intermediate shelf is recommended. Appliance must be fixed from underneath.

Connection

Total connected load 7.2 kW. Connecting cable 1.5 m without plug.

Characteristics

Product name/family

Cooking zone ceramic

Construction type

Built-in

Energy input Electric

Total number of positions that can be used at the same time

Type of control setting devices

Sword knobs

Required niche size for installation (HxWxD)

49 x 680 x 490

Width of the product (mm)

704

Dimensions of the product (mm) 67.0 x 704 x 523

Net weight (kg)

15.000

Gross weight (kg)

16.000

Residual heat indicator

Location of control panel

Hob front

Type of external control possibility

Basic surface material

Color of surface

Black, Stainless steel

Color of frame

Stainless steel

Approval certificates

AENOR, CE

Length electrical supply cord (m)

150.0

Consumption and connection features

Electrical connection rating (W) 7200

Gas connection rating (W)

Current (A)

Voltage (V)

220-240

Frequency (Hz) 60; 50

created on 2014-05-13

Page 1



VI270114
Vario induction cooktop 200 series
Stainless steel control panel
Width 70 cm

created on 2014-05-13 Page 2



