



VI462113
Vario flex induction cooktop 400 series
Stainless steel frame
Width 60 cm

Flex function for combining the rectangular cooking areas
Free positioning of cookware inside combined cooking areas with automatic extension up to 30 cm width
Frying sensor function for temperature control in pans
Easy control of all functions with two color displays
Solid stainless steel control knob
Precision crafting of 3 mm stainless steel
For surface installation with a visible edge or for flush installation
Can be combined perfectly with other Vario appliances of the 400 series

Cooking zones

2 flex induction cooking areas with each 19x23 cm (2200 W, with booster 3700 W), linked together 38x23 cm (3300 W, with booster 3700 W), with automatic extension up to 30x30 cm (3300 W, with booster 3700 W).
 2 flex induction cooking areas 19x23 cm (2200 W, with booster 3700 W), linked together 38x23 cm (3300 W, with booster 3700 W).

Handling

Control knobs with illuminated ring, cooking zone and output level markings.
 Electronic power control in 12 pakāpes (1...12).
 User friendly control with two color display (white / orange).

Features

Flex function for rectangular cooking areas.
 Frying sensor function.
 Booster function.
 Stopwatch.
 Short-term timer.
 Options menu.
 Power management.
 Cooktop-based ventilation control (with suitable hood).
 Integrated WiFi module for digital services (Home Connect).
 The availability of the Home Connect functionality depends on the availability of the Home Connect Services in your country. Home Connect Services are not available in every country – for further information please check: www.home-connect.com

Safety

Operation indicator.
 Pot detection.
 2 stage Hh residual heat indicator for each zone
 Safety shut-off.

Planning notes

Depending on the type of installation (surface-mounted or flush-mounted), the specific location of the cut-out and the knob positions may vary.
 The horizontal positioning of the knobs may be aligned with the specific cooking areas.
 The drawing "Installation of the control knob" must be observed if the panel is more than 23 mm thick (there must be a recess at the rear).

Characteristics

Product name/family
 Cooking zone ceramic

Construction type
 Built-in

Energy input
 Electric

Total number of positions that can be used at the same time
 4

Type of control setting devices
 Required niche size for installation (HxWxD)
 57 x 568-570 x 491-493

Width of the product (mm)
 590

Dimensions of the product (mm)
 57 x 590 x 520

Dimensions of the packed product (HxWxD) (mm)
 123 x 875 x 610

Net weight (kg)
 17.221

Gross weight (kg)
 18.7

Residual heat indicator
 Separate

Location of control panel
 External control

Type of external control possibility
 Basic surface material
 Ceramic

Color of surface
 Black, Stainless steel

Color of frame
 Stainless steel

Approval certificates
 AENOR, CE

Length of electrical supply cord (cm)
 150

EAN code
 4242006289812

Consumption and connection features
Electrical connection rating (W)
 7400

Gas connection rating (W)

Current (A)
 2*16

Voltage (V)
 220-240

Frequency (Hz)
 50; 60

created on 2020-04-20
 Page 1

If combining several Vario appliances of the 400 series, a connection strip VA 420 must be placed between the appliances. Depending on the type of installation, the corresponding connection strip must be provided.
 The bearing capacity and stability, in the case of thin worktops in particular, must be supported using suitable substructures. Take into account the appliance weight and additional loads. Additional instructions for flush installation:

Installation is possible in worktops made of stone, synthetics or solid wood. Heat resistance and watertight sealing of the cut edges must be observed. Concerning other materials please consult the worktop manufacturer.

The groove must be continuous and even, so that uniform placing of the appliance on the gasket is ensured. Do not use discontinuous lining.

The joint width may vary due to size tolerances of the combinations and of the worktop cut-out.

If installing several appliances in individual cut-outs allow for a division bar of minimum 50 mm between the individual cut-outs.

Operates with magnetic (induction) iron pots and pans only. For an optimal heat distribution, the use of sandwich bottom cookware is recommended.

The wok pan WP 400 001 cannot be used with this appliance.

Appliance can be snapped into the worktop from above.

Appliance weight: approx. 17.

Connection

Total connected load 7.4 KW.

Connecting cable 1.5 m without plug.
 Power consumption standby/display off 0.4 W.

Power consumption standby/network 1.7 W.

Please check the user manual for how to switch off the WiFi module.

Color Variants

VI462113
 Stainless steel frame
 Width 60 cm

Optional accessories

GP900001
 Stainless steel frying sensor pan
 GP900002
 Stainless steel frying sensor pan
 GP900003
 Stainless steel frying sensor pan
 GP900004
 Stainless steel frying sensor pan

Installation Accessories

VA420000
 Connection strip for combination with other Vario appliances of the 400 series for flush installation
 VA420010
 Connection strip for combination with other Vario appliances of the 400 series for surface installation

