



**AC200191**  
**Canopy extractor 200 series**  
**Stainless steel and glass**  
**Width 86 cm**  
**Air extraction/recirculation**

Can be integrated invisibly in upper cabinet  
Energy-saving, low-noise fan  
Rim extraction with flat and easy-to-clean glass cover  
Dimmable, neutral white LED light for ideal illumination of the whole cooktop  
Air extraction or recirculation system  
Energy efficiency class A++

#### Output

Odour reduction air recirculation 94 %.

#### Features

Three electronically controlled power levels and an intensive mode.  
Remote control is available as a special accessory.  
Interval ventilation, 6 min.  
Run-on function, 6 min.  
Grease filter saturation indicator.  
Metal grease filter, dishwasher-safe.  
Glass filter cover.  
Neutral white LED light (4000 K), dimmable.  
Lamp output 2 x LED spot 1W.  
Illuminance: 266 lx  
Fan technology with highly efficient, brushless DC motor.

#### Product rating

Energy efficiency class A++ at a range of energy efficiency classes from A++ to E.  
Energy consumption 31.4 kWh/year.  
Ventilation efficiency class A.  
Illumination efficiency class A.  
Grease filter efficiency class D.  
Sound level min. 41 dB / max. 64 dB normal mode.

#### Planning notes

Patented air recirculation module with activated charcoal filter can be installed in the upper cabinet. The activated carbon filter can be changed from the front by simply pulling out the filter drawer.  
The door of the upper cabinet must be fully open in order to change the activated charcoal filter.  
Can be integrated invisibly in upper cabinet.  
Vario cooktops with intensive production of vapours like VR/VP/VF should be placed in the middle beneath the cooker hood (in this case air recirculation is not recommended).  
Clearance above gas appliances min. 65 cm (more than total load gas 12 kW min. 70 cm).  
Clearance above electric appliances min. 50 cm.  
When installing a ventilation hood with air extraction mode and a chimney-vented fireplace, the hood's power supply line needs to feature a suitable safety switch.

#### Connection

Total connected load 172 W.  
Connecting cable 1.0 m with plug.

#### Characteristics

**Product name/family**  
**Color chimney**  
**Typology**  
Traditional  
**Approval certificates**  
CE, Eurasian, G-Mark, Ukraine, VDE  
**Length of electrical supply cord (cm)**  
100  
**Required niche size for installation (HxWxD)**  
418mm x 836.0mm x 264mm  
**Height of the chimney (mm)**  
**Height of product, without chimney (mm)**  
**Minimum distance above an electric hob**  
500  
**Minimum distance above a gas hob**  
650  
**Net weight (kg)**  
10.002  
**Type of control**  
Electronic  
**Number of speed settings**  
**Maximum output air extraction (m3/h)**  
610  
**Boost position output recirculating (m3/h)**  
790.0  
**Maximum output recirculating air (m3/h)**  
**Boost position air extraction (m³/h)**  
800  
**Number of lights (Stck)**  
2  
**Noise level (dB(A) re 1 pW)**  
64  
**Diameter of air outlet (mm)**  
120 / 150  
**Grease filter material**  
Washable aluminium  
**EAN code**  
4242006284787

#### Consumption and connection features

**Connection rating (W)**  
172  
**Current (A)**  
3  
**Voltage (V)**  
220-240  
**Frequency (Hz)**  
50  
**Plug type**  
Gardy plug w/ earthing  
**Installation type**  
Built-in

created on 2020-02-15

Page 1

#### Color Variants

**AC200191**  
**Stainless steel and glass**  
**Width 86 cm**

AC200191  
Canopy extractor 200 series  
Stainless steel and glass  
Width 86 cm  
Air extraction/recirculation  
created on 2020-02-15  
Page 2

